

# Artwork Acceptance Criteria

## Artwork

- 1) Artwork should be with actual size with correct dimensions.
- 2) Artwork should be provided in Adobe Illustrator (.ai) file
- 3) Used picture resolution should be 300 dpi and in layered PSD format. Special colors preferable in separate channels.
- 4) Pantone # should be defined for any special color used in the design.
- 5) White separation should be defined clearly for Full Patch, Registered, Transparent or metallic areas.
- 6) Metallic shades can't be printed on digital routes, so combination of CMYK will be used to achieve that effect.
- 7) Shade reference (EFI/GMG/Sample) should be provided along with artwork.
- 8) Structure information with surface/reverse print should be provided.
- 9) First stable printable dot – 1% for CMYK
- 10) Bleed = 1 mm on all sides

## Text / Fonts / Barcode:

- 1) Artwork should be provided with all texts/fonts converted to outlines, curves, paths.
- 2) Positive text / line thickness should be minimum 0.12mm.
- 3) Negative text / line thickness should be minimum 0.14mm.
- 4) Minimum text size – Positive – 4 point and Reverse – 5 point
- 5) All Negative Texts appearing on multi-color background should be with single color casing.
- 6) Minimum Barcode size should be 30mm (W) x 21mm (H), 80% magnification for verification purpose.

*Customer needs to send shade matching reference or clear instructions to match shades with pantone given in the artwork before processing artwork.*